



Soffit - Fascia - Eavestrough - Siding  
Windows - Doors - Roofing

Ph. 204.221.3131 Fax 204.219.4690  
info@advanceexteriors.com  
Box 147 Grosse Isle, Mb  
ROC 1G0

# Quote Request Form Exterior Doors

Customer Name: \_\_\_\_\_

Address: \_\_\_\_\_

Phone Number: \_\_\_\_\_

Date: \_\_\_\_\_

Supply & Install

Supply Only

Quantity: \_\_\_\_\_

Door Style                      Single Door                      Door+Sidelite                      Sidelite+Door+Sidelite Garden Door

Door Location: \_\_\_\_\_ Is this door from House to Garage?  YES  NO

### Measurements (see information guide on "how to measure a prehung door")

Door Slab Size:                      Width \_\_\_\_\_                      Height \_\_\_\_\_

Door Frame Size:                      Width \_\_\_\_\_                      Height \_\_\_\_\_  
from interior view

Door Jamb depth:                      Width \_\_\_\_\_

Existing Casing Width: \_\_\_\_\_

Outside Brickmold size:                      Width \_\_\_\_\_                      Height \_\_\_\_\_  
from exterior view

Door Slab:	Steel	Fiberglass	Textured Fiberglass	
Panel Style:	4 Panel	6 Panel	Flush	Other _____
Door Glass Insert:	NO Glass	1/3 Glass	1/2 Glass	3/4 Glass    Full Glass
Door Glass Spec	_____			

Location of Hinges:	Left	Right	
Swing Type:	Inswing	Outswing	
Bores:	Single Bore	Double Bore	Other _____

Exterior Slab color:	std. White Finish	Custom _____
Interior Slab color:	std. White Finish	Custom _____
Exterior Frame color:	std. White Finish	Custom _____
Interior Frame color:	std. White Finish	Custom _____
Exterior Door Lite color:	std. White Finish	Custom _____
Interior Door Lite color:	std. White Finish	Custom _____
Exterior Brickmold color:	std. White Finish	Custom _____

IF POSSIBLE, SUBMIT PHOTOS OF THE INTERIOR VIEW & EXTERIOR VIEW OF THE DOOR NEEDING TO BE REPLACED

# HOW TO MEASURE A PREHUNG EXTERIOR DOOR

## DOOR SWING

- From the exterior & with the door shut, look at the side where you can see the door hinge pins
- Whatever side the hinges are on, determines whether the door is Left or Right (LH or RH)
- If the door swings towards the exterior when opened it is an outswing
- If the door swings towards the interior, it is an inswing

## SLAB SIZE

- Provide the width and height of the door slab.

## FRAME SIZE

- From the interior, remove the interior door casing to measure the exterior frame of the door.
  - If removing the casing is not an option, you can measure the interior frame size and add  $\frac{3}{4}$ " per side to the width (so  $1\frac{1}{2}$ " total) as well as,  $\frac{3}{4}$ " at top and bottom to the height for an approximate frame size
- Note: depending on current floor material (vinyl, hardwood, etc) the size might vary slightly between  $\frac{3}{4}$ " and  $\frac{3}{8}$ "  
Please determine your floor thickness to be added into your frame height

## OUTSIDE BRICKMOLD MEASUREMENT

- From the exterior
  - For width measure from outside to outside of the exterior brickmold (the trim)
  - For height, measure from the bottom of the sill to the topside exterior brickmold
  - You can also provide a measurement of the width of the current brickmold (i.e.  $1\frac{1}{2}$ ", 2" etc.)

## JAMB DEPTH

- Measure the thickness of the house wall from interior to exterior not including the interior casing or exterior brickmold \*\*\*BUT do include the depth of any interior drywall or exterior sheathing & rigid insulation on the house